

Case	Ø 3.05 x 14	DO-15	Ø 6.3 x 21	Ø 55 x 36		Case
High voltage rectifiers Voltage V_{RRM} [V]						High voltage rectifiers Voltage V_{RRM} [V]
Current	20 mA	100 mA	1 A...0.3 A	1.8 A	2.5 A	Current
Fast recovery	3000	DD300				3000
	4000		BV4	BY4 (1.0 A)		4000
	6000	DD600	BV6	BY6 (1.0 A)		6000
	8000			BY8 (0.5 A)	Si-A 3000/1350-2.5	8000
	10000	DD1000				10000
	12000	DD1200		BY12 (0.5 A)		12000
	14000	DD1400				14000
	16000	DD1600		BY16 (0.3 A)		16000
	18000	DD1800				18000
	20000					20000
	22000					22000
24000				Si-A 8000/3600-1.8	24000	
		Standard recovery				Standard recovery

DO-4	
Power-Zener-diodes	Leistungs-Zener-
12.5 W *)	
ZX3.9 ... 200	
*) mounted on cooling fin / auf Kühlblech	



Case	Sandwich			Case
Rectifier cells Voltage V_{RRM} [V]				Rectifier cells Voltage V_{RRM} [V]
Current	3 A	6 A	12 A	Current
Standard recovery	50	AG3A	AG6A	50
	100	AG3B	AG6B	100
	200	AG3D	AG6D	200
	400	AG3G	AG6G	400
	600	AG3J	AG6J	600
	800	AG3K	AG6K	800
	1000	AG3M	AG6M	1000
	A = 5.4 B = 5.0 C = 2.3	A = 5.7 B = 5.5 C = 2.3	A = 6.5 B = 6.8 C = 2.3	