

Master Fuse gG 690V & 500V



Master Fuse: gG fuses with very high ratings



Breaking capacity	Size	Cat.Number	Ref.Number	Pack
1250	76	MF76GG69V1250	E302753	1
1600	89	MF89GG69V1600	F302754	1
2000	114	MF114GG69V2000	G302755	1
2500	127	MF127GG69V2500	H302756	1
3200	146	MF146GG50V3200	J302757A	1
4000	159	MF159GG50V4000	K302758A	1
4800	181	MF181GG50V4800	L302759A	1

Characteristics

- High ratings, from 1250 to 4800A
- gG class with rated voltage 690V & 500V
- IEC 60269-1 and 2 compliant
- Dimensions as per section V, IEC 60269-2-1
- Breaking capacity:
160 kA to 690V 50 Hz (1250 to 2500A)
160 kA to 500V 50 Hz (3200 to 4800A)

Applications

- General protection for low voltage panels
- High power protection at 690V&500V
- Backup for circuit breakers
- Blade fuses for power busbar assembly
- Disconnecter, switch or circuit breaker isolation

Fuse and Fusegear complying with the 4 standards: DIN, BS, NF, UL-CSA
Your one-stop shop for the safety of low voltage equipment

Our solutions are fully safe for use in yours!

www.ferrazshawmut.com

From to

1, rue Jean Noël - 69626 Villeurbanne Cedex - France
Tél: 33 (0)4 72 22 66 11 - Fax 33 (0)4 72 22 67 13
374 Merrimack Street Haverhill, MA 01950 - 1998 - USA
Phone : 978-462-6662 - Fax : 978-462-018
www.ferrazshawmut.com

Ferraz Shawmut

CL