

Bezpieczniki IEC - MI5F25V - szybko działające

250 V AC - F: szybko działające - od 0.032 do 20 A - rozmiar: 5 x 20



Prąd (A)	Zdolność wyłączeniowa	Numer katalogowy	Numer referencyjny	Opak.
0,032	35 A 250 V	MI5F25V0,032	D222942Q	100
0,04		MI5F25V0,04	M200732Q	100
0,05		MI5F25V0,05	B201274Q	100
0,063		MI5F25V0,063	L201789Q	100
0,08		MI5F25V0,08	K211011Q	100
0,1		MI5F25V0,1	L200731Q	100
0,125		MI5F25V0,125	A201273Q	100
0,16		MI5F25V0,16	K201788Q	100
0,2		MI5F25V0,2	J211010Q	100
0,25		MI5F25V0,25	A211531Q	100
0,315		MI5F25V0,315	F212042Q	100
0,4		MI5F25V0,4	B211532Q	100
0,5		MI5F25V0,5	Y212564Q	100
0,63		MI5F25V0,63	J213080Q	100
0,8		MI5F25V0,8	G212043Q	100
1		MI5F25V1	D213581Q	100
1,25		MI5F25V1,25	D214087Q	100
1,6		MI5F25V1,6	Z212565Q	100
2		MI5F25V2	J214598Q	100
2,5		MI5F25V2,5	Q215110Q	100
3,15	MI5F25V3,15	R215617Q	100	
4	10 xIn 250 V	MI5F25V4	Z216130Q	100
5		MI5F25V5	W216633Q	100
6,3		MI5F25V6,3	H217150Q	100
8		MI5F25V8	M217660Q	100
10		MI5F25V10	X218175Q	100
12,5		MI5F25V12,5	K218693Q	100
16		MI5F25V16	Y219211Q	100
20		MI5F25V20	A219742Q	100

Bezpieczniki bez zatwierdzeń.

Bezpieczniki DIN - MI5SM25V - średnio zwłoczne

250 V AC - M: średnio zwłoczne - od 0.032 do 20 A - rozmiar: 5 x 20

Prąd (A)	Zdolność wyłączeniowa	Numer katalogowy	Numer referencyjny	Opak.
0,032	80 A 250 V	MI5SM25V0,032	D218158Q	100
0,04		MI5SM25V0,04	Q218675Q	100
0,05		MI5SM25V0,05	D219193Q	100
0,063		MI5SM25V0,063	H219726Q	100
0,08		MI5SM25V0,08	Q222171Q	100
0,1		MI5SM25V0,1	Q222925Q	100
0,125		MI5SM25V0,125	T200715Q	100
0,16		MI5SM25V0,16	H201257Q	100
0,2		MI5SM25V0,2	T201773Q	100
0,25		MI5SM25V0,25	K207147Q	100
0,315		MI5SM25V0,315	J211516Q	100
0,4		MI5SM25V0,4	N212026Q	100
0,5		MI5SM25V0,5	F212548Q	100
0,63		MI5SM25V0,63	R213064Q	100
0,8		MI5SM25V0,8	M213566Q	100
1		MI5SM25V1	L214071Q	100
1,25		MI5SM25V1,25	T214584Q	100
1,6		MI5SM25V1,6	A215096Q	100
2		MI5SM25V2	A215602Q	100
2,5		MI5SM25V2,5	H216115Q	100
3,15	MI5SM25V3,15	E216618Q	100	
4	300 A 250 V	MI5SM25V4	R217135Q	100
5		MI5SM25V5	E218159Q	100
6,3		MI5SM25V6,3	R218676Q	100
8		MI5SM25V8	E219194Q	100
10		MI5SM25V10	J219727Q	100
16		MI5SM25V16	R222172Q	100



Bezpieczniki bez zatwierdzeń.

Bezpieczniki IEC - MI5T25V - zwłoczne

250 V AC - T: zwłoczne - od 0.032 do 20 A - rozmiar: 5 x 20



Prąd (A)	Zdolność wyłączeniowa	Numer katalogowy	Numer referencyjny	Opak.
0,032	35 A 250 V	MI5T25V0,032	C216639Q	100
0,04		MI5T25V0,04	P217156Q	100
0,05		MI5T25V0,05	T217666Q	100
0,063		MI5T25V0,063	D218181Q	100
0,08		MI5T25V0,08	R218699Q	100
0,1		MI5T25V0,1	B216638Q	100
0,125		MI5T25V0,125	N217155Q	100
0,16		MI5T25V0,16	S217665Q	100
0,2		MI5T25V0,2	C218180Q	100
0,25		MI5T25V0,25	Q218698Q	100
0,315		MI5T25V0,315	D219216Q	100
0,4		MI5T25V0,4	E219217Q	100
0,5		MI5T25V0,5	F219747Q	100
0,63		MI5T25V0,63	N222192Q	100
0,8		MI5T25V0,8	G219748Q	100
1		MI5T25V1	J222947Q	100
1,25		MI5T25V1,25	S200737Q	100
1,6		MI5T25V1,6	P222193Q	100
2		MI5T25V2	G201279Q	100
2,5		MI5T25V2,5	R201794Q	100
3,15	MI5T25V3,15	Q211016Q	100	
4	10 xIn 250 V	MI5T25V4	G211537Q	100
5		MI5T25V5	M212048Q	100
6,3		MI5T25V6,3	E212570Q	100
8		MI5T25V8	Q213086Q	100
10		MI5T25V10	J213586Q	100
12,5		MI5T25V12,5	P214603Q	100
16		MI5T25V16	X215116Q	100
20		MI5T25V20	Y215623Q	100

Bezpieczniki bez zatwierdzeń.

Bezpieczniki IEC - MI6F25V - szybko działające

250 VAC - F: szybko działające - od 0.032 do 25 A - rozmiar: 6 x 32

Prąd (A)	Zdolność wyłączeniowa	Numer katalogowy	Numer referencyjny	Opak.
0,032	35 A 250 V	MI6F25V0,032	B219214Q	100
0,04		MI6F25V0,04	D219745Q	100
0,05		MI6F25V0,05	L222190Q	100
0,063		MI6F25V0,063	G222945Q	100
0,08		MI6F25V0,08	Q200735Q	100
0,1		MI6F25V0,1	K217152Q	100
0,125		MI6F25V0,125	P217662Q	100
0,16		MI6F25V0,16	Z218177Q	100
0,2		MI6F25V0,2	M218695Q	100
0,25		MI6F25V0,25	A219213Q	100
0,315		MI6F25V0,315	C219744Q	100
0,4		MI6F25V0,4	E201277Q	100
0,5		MI6F25V0,5	K222189Q	100
0,63		MI6F25V0,63	F222944Q	100
0,8		MI6F25V0,8	P201792Q	100
1		MI6F25V1	P200734Q	100
1,25		MI6F25V1,25	D201276Q	100
1,6		MI6F25V1,6	N211014Q	100
2		MI6F25V2	N201791Q	100
2,5		MI6F25V2,5	M211013Q	100
3,15	MI6F25V3,15	J212045Q	100	
4	10 xln 250 V	MI6F25V4	B212567Q	100
5		MI6F25V5	M213083Q	100
6,3		MI6F25V6,3	G214090Q	100
8		MI6F25V8	L214600Q	100
10		MI6F25V10	T215113Q	100
12,5		MI6F25V12,5	V215620Q	100
16		MI6F25V16	Z216636Q	100
20		MI6F25V20	Q217663Q	100
25		MI6F25V25	A218178Q	100



Bezpieczniki bez zatwierdzeń.

Bezpieczniki IEC - MI6T25V - zwłoczne

250 V AC - T: zwłoczne - od 0.032 do 25 A - rozmiar: 6 x 32



Prąd (A)	Zdolność wyłączeniowa	Numer katalogowy	Numer referencyjny	Opak.
0,032	35 A 250 V	MI6T25V0,032	H216138Q	100
0,04		MI6T25V0,04	F216642Q	100
0,05		MI6T25V0,05	S217159Q	100
0,063		MI6T25V0,063	X217669Q	100
0,08		MI6T25V0,08	G218184Q	100
0,1		MI6T25V0,1	M214095Q	100
0,125		MI6T25V0,125	Q214604Q	100
0,16		MI6T25V0,16	A215625Q	100
0,2		MI6T25V0,2	G216137Q	100
0,25		MI6T25V0,25	E216641Q	100
0,315		MI6T25V0,315	R217158Q	100
0,4		MI6T25V0,4	V218702Q	100
0,5		MI6T25V0,5	W217668Q	100
0,63		MI6T25V0,63	F218183Q	100
0,8		MI6T25V0,8	H219220Q	100
1		MI6T25V1	T218701Q	100
1,25		MI6T25V1,25	G219219Q	100
1,6		MI6T25V1,6	K219751Q	100
2		MI6T25V2	J219750Q	100
2,5		MI6T25V2,5	R222195Q	100
3,15	MI6T25V3,15	M222950Q	100	
4	10 xIn 250 V	MI6T25V4	W200740Q	100
5		MI6T25V5	K201282Q	100
6,3		MI6T25V6,3	Q212051Q	100
8		MI6T25V8	H212573Q	100
10		MI6T25V10	S213088Q	100
12,5		MI6T25V12,5	L213588Q	100
16		MI6T25V16	N214096Q	100
20		MI6T25V20	R214605Q	100

Bezpieczniki bez zatwierdzeń.